


serie  
**UR-53**



## BRIDA DOBLE CÁMARA PARA TUBERÍA DE PVC Y POLIETILENO

FLANGE ADAPTOR  
FOR PVC AND POLYTHENE PIPES



### Características:

- Desviación angular: 3°
- Temperatura de utilización: +0°C / +60°C
- El sistema de amarre soporta los esfuerzos debidos a la presión hidráulica hasta el límite marcado por la norma EN 12842. No está diseñado para soportar los esfuerzos mecánicos de las tuberías.
- Montaje vertical ascendente desaconsejado.
- Válido para utilizar con tuberías de PVC orientado.

### Specifications:

- Maximum angular deflection: 3°
- Temperature for usage: +0°C / +60°C
- The gripping system reaches the efforts of hydraulic pressure stated as per norm EN12842. It is not designed to hold the mechanic efforts of the pipes.
- Upward vertical assembly non advisable.
- Valid to use on PVC-0 pipes.

REF.	Ø	DN	L
UR-53-DE063	63	50-60-65	72
UR-53-DE075	75	50-60-65	72
UR-53-DE090	90	80	76
UR-53-DE110	110	100	80
UR-53-DE125	125	125	80
UR-53-DE140	140	125	80
UR-53-DE160	160	150	90
UR-53-DE200	200	200	100

- Instalación rápida y sencilla.
- Cierre estanco y amarre mecánico.
- Bloqueo mecánico mediante un anillo de sujeción para evitar el movimiento axial de la tubería.
- Amplia gama de diámetros que cubre tubos desde 63 hasta 200 milímetros.
- Adecuado para tubos de presión de PVC y PVC orientado.
- Presión de trabajo PN-10 y PN-16.
- Barrenado EN 1092-2 PN10 / PN16 (para DN-200, doble barrenado PN-10 y PN-16).
- Fundición nodular GGG-50.
- Revestimiento EPOXI de 250µ de media.
- Juntas de goma EPDM.
- Anillo de sujeción de latón.

- Easy and fast installation.
- Leakproof and mechanical locking.
- Mechanical locking by a grip ring in order to avoid pipe's axial movement.
- Wide range of diameters covering pipes from 63 to 200 millimeters.
- Suitable for PVC and PVC-0 pressure pipes.
- PN-10 and PN-16 operating pressure.
- Flanges according to EN 1092-2 PN-10 / PN-16 (for DN-200, double drilling PN-10 and PN-16).
- GGG-50 nodular cast iron.
- 250µ EPOXY average coating.
- EPDM rubber seal.
- Grip ring made of brass.

HISPÁNICA DE VALVULERÍA, S.L.

